

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 902040

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 6 only of T 28-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Ford, Under Contract #44 dated
May 30, 1854 (DCSO records, Volume 12 Page 5221)

Set a post, cor. of secs. 5 and 6, from which
A B.Oak 4" dia., bears S.30°W., 15 lks. dist.
A W.Oak 5" dia., bears S.4°E., 17 lks. dist.

GLO survey by Fred Mensch, Under Contract #109 dated 1924
(DCSO records, Volume 14 Page 5876)

Intersect the point for the cor. established by Ford for
standard cor. of secs. 5 and 6, located on line between
original Ford cors. for latitude and by Hathorn's record tie
from the Hathorn standard cor. of secs. 5 and 6 for departure.
At the true cor. point thus determined, Set an Iron post, 3
ft. long 2" dia., 12" in the ground, in mound of stone, for
standard NE cor. of sec. 6 only, with brass cap marked

S 6
T 28 S
R 7 W
S C
1924

from which
A B.Oak 5" dia., bears S.71½°W., 39 lks. dist., marked
S C T28S R7W S6 BT.
A Fir 26" dia., bears S.48°W., 86 lks. dist., marked
S C T28S R7W S6 BT.

The new NW cor. of sec. 5 on the S. bdy. of sec. 32, bears
S.4°22'E., 5.82 chs. dist.
The cor. established by Hathorn for standard cor. of secs 5 &
6, restored as angle point, bears S.38°21'W., 7.38 chs.

H.L. Eppstein, Co. Surveyor - Wit: B.A. Lane; Fitzpatrick;
Hollis Green - June 1930 - C.S. File 14/59; M 1-73 and
"old" corner book, Page 111

Found - Standard govt post set by Minsch in 1924.
Fir 24" dia., bears S.47°W., 56.3 ft.
B.Oak 5" dia., bears S.72°W., 26.0 ft.

Doug. County Surveyors Office - James Byron, Deputy - Milo
Godfrey; Clete Putnam - Feb/March 1961 - C.S. File 49/79-37

(Cont. Next Page)

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 902040

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 6 only, T28-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found - Brass cap at corner and stump of SW BT.
New BTs - 12" R.Fir bears N.53½°W., 35.5 ft. scribed NE S6 CS BT.
5" R.Fir bears S.13°W., 15.7 ft. scribed NE S6 CS BT.

Fd. OK by McLind, surveyed Dec.'96 thru Feb.'98 - M 128-40

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/28/1998 - C.S. File 66/2-42

Found - 2½" dia., brass cap on a 2" O.D. iron pipe, protrudes 15" above a mound of sandstone, properly marked. 1924
26" now 27" dia., 2' high rotted D.Fir stump with scribing visible "S6 BT" bears S.48°W., 56.8' (Agrees with rec.) 1924
12" now 20" dia., D.Fir with a fully healed double blaze, bears N.55½°W., 35.5'. (Rec. N.53½°W., 35.5') 1961
5" now 15" dia., D.Fir with a fully healed double blaze, bears S.13°W., 15.7'. (Agrees with rec.) 1961

Set - More sandstone added to mound, brass cap iron pipe now protrudes 5" above mound.
10" dia., Madrone, double blazed and scribed "NE S6 CS BT" bears S.69½°W., 6.5'.
8" dia., W.Oak, double blazed and scribed "NE S6 CS BT" bears N.25°E., 29.0'.