

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 902050

PRIMARY CORNER DESCRIPTION Angle Point on old N. Bdy. Sec. 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Nathaniel Ford under Contract #44 dated May 30, 1854 (DCSO records, Volume 12 Page 5221)

-----  
Set ¼ sec. post, from which  
(no trees listed in field notes)

GL0 survey by Fred Mensch, Contract #109 dated 1924 (DCSO records, Volume 14 Page 5875)

-----  
Point for cor. established by Ford for the ¼ sec. cor. of sec. 32, located by Hathorn's record tie from Hathorn ¼ sec. cor. of sec. 32. (SEE DCSO records, Vol. 12 Pag 5225)  
At the exact cor. point, Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for angle point, with brass cap marked:

AP  
1924

from which

A Fir 18" dia., bears S.40°E., 15 lks. dist., mkd. AP BT.

A Fir 8" dia., bears S.27½°W., 48 lks. dist., mkd. AP BT.

The ¼ sec. cor. of sec. 32, established by Hathorn, bears S.33°57'W., 5.50 chs.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam - Feb/March 1961 - C.S. File 49/79-39

-----  
(Angle Point, N.33°57'E., 5.50 chs. from S ¼ S32)

Found - Brass cap.

SE BT, now snag, shows good scar.

SW BT, now stump.

New BTs - 7" Cedar bears N.57°E., 13.4 ft. scribed AP CSBT.

8" R.Fir bears N.34°W., 3.5 ft. scribed AP CS BT.