

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 902070

PRIMARY CORNER DESCRIPTION Angle Point, old N. Bdy. S. 5 T28-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Nathaniel Ford, Deputy under Contract #44 dated May 30, 1854 (DCSO records, Volume 12 Page 5221)

-----  
Set a post, cor. of secs. 32 and 33, from which  
A B.Oak 8" dia., bears N.35°E., 14 lks. dist.  
A Laurel 20" dia., bears N.5°W., 60 lks. dist.

GL0 survey by Fred Mensch, Deputy under Contract #109 dated 1924 (DCSO records, Volume 14, Pages 5873-74)

-----  
Intersect the point for cor. of secs. 32 and 33, established by Ford, located by record measurements from the original bearing trees. The marks on the NE tree legible. The blazes on the NW tree are plain, but the marks are weathered and decayed away. At the exact cor. point, Set an Iron post, 3 ft. long, 1" dia., 28" in the ground, for angle point, with brass cap marked:

AP

1924

from which (new bearing trees)

A Fir 14" dia., bears S.41°E., 35 lks. dist. mkd. AP BT.

A Fir 8" dia., bears S.50°W., 11 lks. dist. mkd. AP BT.

Original NE bearing tree, an Oak 16" dia., bears N.35°E., 14 lks dist.

Original NW bearing tree, a Laurel 24" dia., bears N.5°W., 60 lks. dist.

(The cor. of secs. 32 and 33 established by Hathorn, bears S.36°25'W., 4.21 chs. dist. - See Vol. 12 Page 5225)

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam - Feb/March 1961 - C.S. File 49/79-31

-----  
Found - Iron pipe with brass cap mkd: "AP 1924"  
14" Fir stump S.41°E., 23.1 ft. shows good scar.  
8" Fir stump S.50°W., 7.3 ft. uprooted & lying face down.

Did not look for two original trees.

New BTs - 22" Laurel N.46¾°E., 28.5 ft. mkd: "AP CS BT".

12" Cedar N.54°W., 66.4 ft. mkd: "AP CS BT".