

TOWNSHIP 27 RANGE 07 POINT IDENTIFIER # 902100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 4 only, T28-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by F. Mensch, Contract #109 dated 1924 (DCSO records Vol. 14 Page(s) 5871)

Apportioned distance.
Set an iron post, 3 ft. long, 1 in. dia., 28 ins. in the ground, for standard $\frac{1}{4}$ sec. Cor., with brass cap mkd:

SC $\frac{1}{4}$ S4

from which

An Ash 10 ins. dia., bears S.85 $\frac{1}{4}$ °E., 206 lks., mkd: SC
 $\frac{1}{4}$ S4 BT.

A B.Oak, 6 ins. dia., bears S.75 $\frac{1}{2}$ °W., 208 lks., mkd: SC
 $\frac{1}{4}$ S4 BT.

The cor. Established by Hathorn for the standard $\frac{1}{4}$ sec. cor. of sec. 4, restored as angle point, bears S.36°13'W., 1.94 chs.

Fd. brass cap & BTs, by H. Northcraft, 11/74 M54-55
Fd. brass cap, by L. Dolan, 6/81 - M 73-27 & M88-30
Fd. ok by J. Artman, 4/90 - M110-5