

PRIMARY CORNER DESCRIPTION North Cor. Secs. 2 & 3, T28-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records Vol. 12 Page(s) 5219)

-----

Set a post, corner of secs. 2 & 3, made a trench and drove a charred stake 12 ins. long, in the center, as per instructions for standard corner

GLO survey by F. Mensch, Contract #109 dated 1924 (DCSO records Vol. 14 Page(s) 5867)

-----

Intersect the point for Ford's standard corner of secs. 2 & 3, located by Hathorn's record tie from Hathorn's corner of secs. 34 & 35.

At the exact cor.

Set an iron post, 3 ft. long, 2 ins. dia., 28 ins. in the ground, for standard corner of secs. 2 & 3, w/brass cap mkd:

S3:S2  
 T28S:R7W  
 1924

From which (new bearing trees):

A wild apple, 5" dia., bears S.79°E., 344 lks., mkd: SC  
T28S R7W S2 BT.

A wild apple, 8" dia., bears S.80½°W., 411 lks., mkd:  
SC T28S R7W S3 BT.

Hathorn's cor. secs. 34 & 35 bears S.84°53'W. 7.30 chs

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/12/1998 - C.S. File 66/2-25

-----

Fd - 2" O.D. IP 3" below ground. 2½" brass cap and 12" of IP are found South of corner, loose on top of ground in fence line. Cap is properly mkd. 1924

5" now 7" dia., 6" high Apple stump, no blazes or scribing vis., bears S.79°E., 227.0', agrees w/rec. 1924

1924 GLO BC/IP for the South Cor. of Secs. 34 & 35 only, agrees w/rec. "S.84°53' 481.8 ft" 1924

1924 SW BT not found.

Set- 2 3/8" dia., BC on a 1 3/8" O.D. by 32" long IP is set at plumb position of found 24" long IP in ground with flanges, BC/IP is set 2" below ground, pieces of 1924 BC/IP are below ground along S&E edges of BC/IP. Cap stamped:

DOUGLAS COUNTY SURVEYOR'S

<u>T 28 S</u>	R
S 3 S 2	7
1998	W

TOWNSHIP 27 RANGE 07 OFFICE \_\_\_\_\_ (Cont. next page)  
POINT IDENTIFIER # 902160

PRIMARY CORNER DESCRIPTION Cor. Secs. 2 & 3 only (N) T28-7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

10" dia., Apple double blazed & scribed "X CS BT"  
bears N.79°E., 171.7', (Note: BT out of Sec.)  
5/8" I.R. with DCSO alum cap stamped "BO 1" bears  
South, 46.0', set in fence line 3" above ground.  
Top point of barn (old octagon shaped) bears N.15°W.  
See sketch in file.