

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heyden, Deputy Surveyor, under contract #656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5289)

Set Yew post 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor. mkd. ¼ S. on W. face, from which
 A Hemlock 8" dia., bears N.15°E., 60 lks. mkd. ¼ S BT.
 A Hemlock 10" dia., bears N.70°30'W., 56 lks. dist. mkd. ¼ S BT.

Weyerhaeuser corner report, no surveyor's name or stamp, no date of visit - C.S. File 58/271-5

Per note on file:

"The attached corners were visited by Douglas Co. crews with insufficient evidence available for remonumenting the corners. Weyerhaeuser information was not based on "found" original evidence and the County crew disagreed with many of Weyerhaeuser's bearing and distance to their set monument." July 1983 V. Laugen - This information added to the corner report on 9/20/2001. DCSO
Pipe present at corner.
 11" Yew N.70½°W., 37.0 ft.
 60" Fir S.47½°E., 24.5 ft.

Survey by Robert C. Adamek - For: Weyerhaeuser Co. - Nov. 1975 - C.S. File 58/76 and M 58-54

Found - A 12" Yew which bears N.70°30'W., 56 lks. Visible scribing, original BT.
Set a 3/4" Iron pipe, from which
 8" Hemlock bears N.13°30'W., 44.6 ft.
 24" Hemlock bears S.31°30'E., 44.4 ft.

BLM resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #903, surveyed March 1976 (DCSO records Vol. 39 Page(s) 15714-15)

The ¼ sec. cor., perpetuated and recorded by Adamek, 1975, monumented with an iron pipe, 3/4" dia., firmly set, projecting 10" above ground, from which the remains of the original bearing trees:
 A Yew 12" dia., bears N.70½°W., 56 lks. dist., with scribe marks ¼ S visible on open blaze. (Rec. Hemlock)
and a bearing tree mkd. by Adamek
 A Hemlock 8" dia., bears N.13½°W., 67½ lks. dist., with a galv. nail with "W" embossed on head, at base.
continued next page

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 20" in the ground,
over the iron pipe, and in a mound of stone, 2 1/2 ft. base to
top, with brass cap mkd:

T 27 S
R 9 W | R 8 W
 | 1/4 S 19
 1976

from which new bearing trees

A Hemlock 6" dia., bears N.10 1/2°E., 125 lks. dist. mkd. 1/4
S19 BT.

A Hemlock 9" dia., bears S.19 3/4°E., 119 lks. dist., mkd.
1/4 S19 BT.

Tony Hostetter - For: Weyerhaeuser - June 2014 - C.S. File
65/86-7

Found - 1976 BLM brass cap as described DCSO Vol. 39, PG.
15714. From which:

16" Hemlock, face evident, WEYCO tag, bears;
N.13 1/2°W., 44.6 ft.

New BTs- 15" Fir, scribed "S19 1/4 BT", BT Tag, bears S.90°E.,
34.2 ft to spike.

10" Fir, scribed "S19 1/4 BT", BT Tag, bears S.8°E.,
4.8 ft to spike.

17" Alder, scribed "S 19 1/4 BT", BT Tag, bears
N.04°W., 14.6 ft to spike.