

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 100377

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only, T27-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Samuel W. Lackland,, Deputy Surveyor, under Contract #660, dated May 31, 1896 - surveyed June/Aug. 1897  
C.S. File 64/76-3

-----  
At point of intersection (3.01 chs. S. of the cor. of secs. 13, 18, 19 and 24) I set a sandstone 16x14x4 ins., 11" in the ground for closing cor. of secs. 13 and 24 marked C C on W. with 3 grooves on N. and S. faces, from which  
A Yew 7" dia., bears N.36°W., 30 lks. dist.mkd. T27S R9W S13 BT.  
A Hemlock 40" dia., bears S.64°W., 11 chs. dist., mkd. T27S R9W S24 BT.

Survey by Robert C. Adamek - For: Weyerhaeuser Co. - (Elk Wallow Survey) July 13, 1977 - C.S. File 58/139 & M 66-12

-----  
The original stone and two BTs were found by Williams and Lester in 1969:  
12" Yew bearing N.36°W., 19.8 ft., down.  
Fir snag bearing S.64°W., 7.2 ft.  
Additional references:  
16" Hemlock bears N.84½°W., 32.0 ft.  
14" Hemlock bears S.27°W., 40.7 ft.