

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 100477

PRIMARY CORNER DESCRIPTION C C for Secs. 12 & 13, T27-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Samuel W. Lackland, Deputy Surveyor, Contract #660, dated May 31, 1896, surveyed June/Aug. 1897 - C.S. File 64/76-3

-----

At point of intersection (3.15 chs. S. of cor. to secs. 7, 12, 13 & 18), Set a sandstone 18x12x7 ins., 12" in the ground for closing cor. of secs. 12 and 13 marked C C on W. with 4 grooves on S. and 2 grooves on N. face, from which

A Yew 12" dia., bears N.5°W., 10 lks. dist. mkd. T27S R9W S12 BT.

A Hemlock 28" dia., bears S.20°W., 33 lks. dist. mkd. T27S R9W S13 BT.

Survey by Robert C. Adamek - For: Weyerhaeuser Co. - (Elk Wallow Survey) July 13, 1977 - C.S. File 58/139 and M 66-12

-----

Found - One orig. BT in 1975, which is a 12" Yew bearing N.5°W., 10 lks. Tree is down and has visible scribing on underside.

Set a 1" Iron pipe, from which  
10" D.Fir bears N.67½°W., 14.5 ft.  
10" Hemlock bears S.87°E., 17.6 ft.

This corner does not close on the township line.