

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heyden, Deputy Surveyor, under contract #656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5291)

Set yew post 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 7, 12, 13, and 18, marked T27S S7 on NE.; R8W S18 on SE.; S13 on SW.; and R9W S12 on NW. faces, with 4 notches on S. and 2 notches on N. edges, from which
A Fir 36" dia., bears N.35°45'E., 16 lks. dist. mkd. T27S R8W S7 BT.
A Fir 30" dia., bears S.20°E., 45 lks. dist. mkd. T27S R8W S18 BT.
A Hemlock 5" dia., bears S.64°W., 40 lks. dist. mkd. T27S R9W S13 BT.
A Hemlock 8" dia., bears N.31°W., 36 lks. dist. mkd. T27S R9W S12 BT.

GLO survey by Samuel W. Lackland, Deputy Surveyor, Contract #660, dated May 31, 1896, surveyed June/Aug. 1897 - C.S. File 64/76-3

(Found corner as described above) I efface the markings thereon referring to the secs. in R9W.

Survey by Robert Adamek - For: Weyerhaeuser Co. - (Elk Wallow Survey) July 13, 1977 - C.S. File 58/139 and M 66-12

Set by single proportion, a 1½" brass cap monument, from which
A 10" Hemlock bears S.84°W., 30.8 ft. scribed STD CNR RP.
A 6" Hemlock bears S.49°E., 22.3 ft. scribed STD CNR RP.