

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heyden, Deputy Surveyor, under contract #656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5291)

Set a Yew post 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor. ¼ S on W. face, from which
 A Chinquapin 10" dia., bears N.25°E., 15 lks. dist. mkd. ¼ S BT.
 A Fir 5" dia., bears N.30°30'W., 50 lks. dist. mkd. ¼ S BT

Survey by Robert C. Adamek - For: Weyerhaeuser Co. - (Elk Wallow Survey) July 13, 1977 - C.S. File 58/139 & M 66-12

Set by single proportion, a "W" nail in a large buried log for the corner. Also scribed "¼ S7" in a Cedar log lying over the point. Referenced the point as follows:
 4" D.Fir bears N.26°W., 37.2 ft.
 24" D.Fir stub bears S.38°W., 3.2 ft.
The area has recently been logged and scarified.