

PRIMARY CORNER DESCRIPTION NW. Cor. for Sec. 6, T28-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5785)

Set post cor. T 28 S., Rs. 8 and 9 W., from which
 A Fir 8" dia., bears S.10°E., 78 lks. dist.
 A Fir 40" dia., bears S.12°W., 120 lks. dist.

GLO survey by William P. Heyden, Deputy Surveyor, under contract #656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5284)

Standard cor. to T 28 S, Rs. 8 & 9 W. I determine this point by running 40 chs. West from the standard ¼ sec. cor. on North side of sec. 6; and by running North 40 chs. from ¼ sec. cor. bet. secs. 1 & 6, T28S Rs. 8 & 9 W. I fixed the locus for said cor. from the orig. witness trees as described in the notes furnished by the Surveyor General, to wit:
 A Chinquapin 12" dia., now 16", bears S.85°W., 23 lks.
 A Chinquapin 12" dia., now 14", bears S.70°E., 36 lks.

(Note: I could find no notes that listed the Chinquapin BTs described by Heyden. V.Laugen, April 1997)

Douglas Co. Surveyors Office - John M. Powell, and crew - 1970 - C.S. File 54/113-4A

Looked for, not found.
 Could not find any evidence of this corner. This area disturbed by logging.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2012, surveyed April 2002/March 2003 - (DCSO rec. Vol. 54 Page(s) 21182)

The point for the cor. of Tps. 28 S., Rs. 8 & 9 W., on the Sixth Standard Parallel South, at proportionate distance, there is no remaining evidence of the original corner. Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, in a collar of stone, with brass cap mkd.

T27S R8W
 S 31
 S 1 | S 6
 R9W R8W
 T28S
 2002

continued next page

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 107100

PRIMARY CORNER DESCRIPTION NW. Cor. for Sec. 6, T28-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which

A fir, 10" diam., bears S.59°E., 7.2 ft., mkd. T28S R8W
S6 BT.

A fir, 11" diam., bears S.14½°W., 19.3 ft., mkd. T28S R9W
S1 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)
driven at the base right side-center, unless otherwise
described in the corner description

Deposit a magnet in a white plastic case at the base of the
stainless steel post.