

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 31 & 32 (South)

Alias _____ Description Also Western terminus S 32, T27½-8
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William P. Heyden, Deputy Surveyor, under contract #656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5282-83)

Set a Yew post 3 ft. long, 4" sq., 24" in the ground, for standard cor. to secs. 32 and 31 marked S C T27S R8W on N.; S31 on W.; and S32 on E. faces, with 1 groove on W. and 5 grooves on E. faces; from which
A Fir 30" dia., bears N.54°E., 50 lks. dist. mkd. T27S R8W S32 BT.
A Fir 30" dia., bears N.5°W., 40 lks. dist. mkd. T27S R8W S31 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; J. Fee, crew - July/Aug. 1957 - C.S. File 49/5

Found - Orig. N.5°W., 26.4 ft., 30" Fir, now snag. Good bark scribing.
Also find Fir stump 36", bark gone, bears N.75°E., 33.0 ft. (Rec. 30" Fir N.54°E., 33.0 ft.)
Position of corner determined by the one remaining BT, from which a real old 3"x3"x36" Ewood stake bears S.38½°E., 15.0 ft., no scribing on stake.

Set Brass cap at cor. mkd: County Surveyors Office
T 27 S R 8 W
31 | 32
6
T 28 S R 8 W
1957

New BTs- 6" Ewood bears N.49°E., 9.0 ft. scribed T27S R8W S32 CS BT.
8" Hemlock bears N.73°W., 59.0 ft. scribed T27S R8W S31 CS BT.
24" Hemlock bears S.2½°W., 45.0 ft. scribed T28S R8W S6 CS BT.

BLM Resurvey by C. Albert White; John M. Jelley; James E. Jelley, Cadastral Surveyors, Under group #466, Surveyed Sept/Oct. 1961 - (DCSO records Vol. 30 Page(s) 12865-66)

The standard cor. of secs. 31 and 32, on the S. bdy. of T27S R8W, monumented by the DCSO with an iron post, 1" dia., protruding 12" above ground, with brass cap mkd. as in 1957, from which the original bearing trees, marked by Heydon in 1896:
A Fir 42" dia., bears N.5°W., 40 lks. dist. mkd. in the bark, T R8W, and other illegible scribe marks. Add the marks SC BT in the bark. (Cont. Next Page)

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 31 & 32 (South)

Alias _____	Description <u>Also Western terminus S. 32, T27½-8</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2500 admin file No. 1201, Surveyed April/May 2012 - (DCSO records Survey plat 2012-1 A&B & Vol. 58 Page(s) 22763-4)

The standard cor. of secs. 31 & 32, on the S.bdy to T27S R8W identical with western terminus and cor. of sec. 32 T27½S R8W., monumented with an iron post, 2½" dia., firmly set, bent S buried 24" below ground surface with a bras cap mkd: COUNTY SURVEYORS OFFICE T27S R8W SEC. 31 32 6 T28S R8W 1957), with brass cap (properly) mkd.

from which the remains of an orig. BT mkd by Heydon

A sawed fir stump 36" dia., bears N.5°W., 26.4 ft. with no marks visible.

and the remains of a BT mkd by Byron in 1957

A Roothole bears S.5°W., 44.9 ft. alongside of which is an uprooted, burnt, sawed, decayed hemlock stump, size indeterminate, with fragmentary scribe marks visible on a partially healed blaze.

and the remains of BTs mkd. by White et al.

A sawed, decayed fir stump, 43" dia., bears N.80½°E., 45.5 ft. with a healed blaze.

A sawed, decayed fir stump, 30" dia., bears S.42°E., 120.1 ft. with scribe marks 6 AP B visible on an open blaze. (Rec. S.43°E., 122.1 ft.)

and the remains of a reference tree mkd by person(s) unknown

A sawed fir stump, 48" dia., bears N.15¾°E., 50.9 ft. with no marks visible, a nail stamped "W" driven in base facing the cor., and a metal tag.

and new BTs

A fir, 9" dia., bears N.53°E., 23.6 ft., mkd: T27S R8W S31 BT.

A fir, 11" dia., bears N.63¾°E., 9.4 ft., mkd: T27S R8E S31 BT.

Reset iron post, 28" long, 24" in ground, add marks 2012 to cap, and bury county monument alongside the iron post.