

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5339)

Set a yew post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 29, 30, 31, & 32, marked T27S S 29 on NE, R8W S 32 on SE, S 31 on SW, S 30 on NW faces, with 1 notch on S & 5 notches on E edges; from which
A fir, 14" dia. bears N.23°E. 36 lks. mkd: T27S R8W S29 BT
A fir, 40" dia., bears S.46½°E., 42 lks., mkd: T27S R8W S32 BT.
A fir, 36" dia. bears S.47°W. 18 lks. mkd: T27S R8W S31 BT
A hemlock, 8" dia., bears N.50°W., 13 lks., mkd: T27S R8W S30 BT.

Weyerhaeuser corner report, no surveyor's name or stamp, no date of visit - C.S. File 58/271-12

Per note on file: "The attached corners were visited by Douglas Co. crews with insufficient evidence available for remonumenting the corners. Weyerhaeuser information was not based on "found" original evidence and the County crew disagreed with many of Weyerhaeuser's bearing and distance to their set monument." July 1983 V. Laugen - This information added to the corner report on 2/11/2008. DCSO
From corner point: 30" Fir, bears N.35°E., 27.6 ft.
60" Fir, bears S.45°E., 30.9 ft.
52" Fir, bears S.50°W., 13.7 ft.
70" Fir, bears N.20°W., 7.5 ft.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Karen Reed - 4/26/1982 - C.S. File 61/30-26

Found - Orig. 14" now 18" fir stump which I open & find scribed "BT"
Orig. 40" now 56" fir stump which I open & find scribed "BT"
Orig. 36" now 47" fir stump with good scar.
Orig. 8" now 13" hemlock stump with good scar.
Remainder of tree lying alongside shows scribed "30 T27S R8W WC" in previously opened blaze.
Set - Using all four orig. BTs I SET 1"x30" IP with brass cap attached marked "Douglas Co Surveyor T27S S30 S29 S31 S32 R8W 1982".

continued next page

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

The corner location matches record bearings to all four BTs and fits the distances fairly close if the distance is taken to the face of the tree. Bearings and distances used to set cor. are as follows:

18" fir stump bears N.23°E., 24.6 ft. to face. (Rec. 23.8 ft)

56" fir stump bears S.46½°E., 28.2 ft. to face (rec. 27.7 ft.)

47" fir stump bears S.47°W., 11.9 ft. to face. (Rec. 11.9 ft)

13" hemlock stump bears N.50°W., 8.9 ft. to face. (Rec. 8.6 ft.)

Brass cap protrudes 12" out of ground.

New - Set spike in top of said 18" fir stump bears N.23°E., 25.0 ft to spike.

Set spike in top of said 56" fir stump bears S.46½°E., 28 8 ft. to spike.

Set spike in top of said 47" fir stump bears S.47°W., 12.0 ft. to spike.

Set spike in top of said 13" hemlock stump bears N.50°W., 9.1 ft. to spike.