

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5342)

-----  
Set a yew post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 19, 20, 29, & 30, marked T27S S 20 on NE, R8W S 29 on SE, S 30 on SW, S 19 on NW faces, with 2 notches on S & 5 notches on E edges; from which  
A fir, 48" dia. bears N.55°E. 84 lks. mkd: T27S R8W S20 BT  
A hemlock, 24" dia., bears S.41°E., 105 lks., mkd: T27S R8W S29 BT.  
A hemlock, 12" dia., bears S.48°W., 87 lks., mkd: T27S R8W S30 BT.  
A hemlock, 24" dia., bears N.12°W., 45 lks., mkd: T27S R8W S19 BT.

Weyerhaeuser corner report, no surveyor's name or stamp, no date of visit - C.S. File 58/271-5 & 12

-----  
Per note on file:  
"The attached corners were visited by Douglas Co. crews with insufficient evidence available for remonumenting the corners. Weyerhaeuser information was not based on "found" original evidence and the County crew disagreed with many of Weyerhaeuser's bearing and distance to their set monument." July 1983 V. Laugen - This information added to the corner report on 2/11/2008. DCSO  
From pipe at corner point: 4" hemlock N.19½°E., 28.4 ft.  
3" hemlock S.18°E., 7.1 ft.  
34" cedar S.15°W., 21.0 ft.  
38" hemlock N.09½°W., 28.7 ft.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Terrie Plouff - John Powell - 4/29/1982 - C.S. File 61/30-29

-----  
Found - Unrecorded 1/2" I.P. firmly set protruding 3" out of ground. From Which:  
Orig. 48" now 53" fir with well healed double blaze bears N.55°E., 58.6 ft. (rec. 55.4 ft.) Due to several large windfalls my dist. was taken from approx. 10 ft. above ground at both ends, which could account for difference noted.  
Orig. 24" now 30" hemlock with scribed "R8W" visible in partially healed blaze bears S.41°E., 71.4 ft. (Rec. 69.3 ft.)  
Orig. 12" now 24" hemlock windfall lying in approx. correct location I can't see tree from cor. due to several large down trees. continued next pg

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Orig. 24" hemlock stump with scribed "27S 8V"  
visible in partially healed blaze, bears N.12°W.,  
29.7 ft.

Unrecorded 4" fir with Weyerhaeuser "W" nail bears  
S.22°E., 7.0 ft.

Set - At the location of the found 1/2" I.P. I SET a  
1"x30" I.P. with brass cap attached and  
protruding 10" out of ground. Cap is mkd.  
"Doug. County Surveyors Office T27S S19 S20 S30  
S29 R8W 1982"

Sketch of accessories in C.S. file.