TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5351)

Set fir post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 5, 6, 7, & 8, 150 ft. above river, marked T27S S 5 on NE, R8W S 8 on SE, S 7 on SW, S 6 on NW faces, with 5 notches on S & E edges; from which

A laurel, 14" dia., bears N.52°E., 75 lks., mkd: T27S R8W S5 BT.
A fir, 16" dia. bears S.80°E., 43 lks. mkd: T27S R8W S8 BT
A hemlock, 20" dia., bears S.65°10'W., 24 lks., mkd: T27S R8W S7 BT.
A cedar, 12" dia., bears N.32°30'W., 122 lks., mkd: T27S R8W S6 BT.

Douglas Co. Surveyors Office - John Powell - Willie Penley - J. Heritage - 10/20/1970 - C.S. File 54/119-6

Found - 12" Cedar, now down, N.32½°W. 80.5 ft., faint scribe 27 8"
20" Hemlock, now down, S.65°W., 15.8 ft., tree buried.
No trace of NE nor SE BTs.

Set - Brass Cap at Cor. mkd: T27S R8W County Surveyors

S 6	S 5	Office
S 7	S 8	1970

New BTs- 6 Chinquapin S.53°E. 13.8 ft. Mkd: T275 R8W S8 CS BT
16" D.Fir S.32°W. 23.6 ft. Mkd: T27S R8W S7 CS BT.
26" D.Fir N.48°W. 52.2 ft. Mkd: T27S R8W S6 CS BT.
No trees available to the NE