

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6; 31 & 32, T26-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by - A. R. and S.C.Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 11 Page(s) 4643)

Cor. to secs. 5, 6, 31 and 32. Made and set post, 4 ft. long, 4" sq. firmly in the ground, from which
A Fir 6" dia., bears N.25°E., 48 lks. dist.
A Fir 48" dia., bears S.40°W., 18 lks. dist.
A Hemlock 5" dia., bears N.65°W., 33 lks. dist.
A Hemlock 6" dia., bears S.70°E., 28 lks. dist.

GLO survey by William P. Heyden, Deputy Surveyor, under contract #656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5337)

Sec. Cor., 5, 6, 31 and 32, not being able to find the post, I determine the point from the bearing trees as described by the surveyor general, where I set Fir post 3 ft. long, 4" sq., 24" in the ground mkd. T26S S32 on NE.; R8W S5 on SE.; T27S S6 on SW.; and S31 on NW. faces with 5 notches on E. and 1 notch on W. edges, witnessed by original trees as described by the surveyor general.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #638, surveyed May\July 1967 (DCSO records Vol. 34 Page(s) 14174-75)

The Sec. Cor., determined at record bearing and distance from the remaining original bearing trees:

A Fir snag 12" dia., bears N.25°E., 48 lks. dist. with fragmentary scribe marks visible on partially opened blaze.

A Fir 75" dia., bears S.40°W., 18 lks. dist., with frag. scribe marks visible on weathered bark blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap mkd:

T 26 S R 8 W

S 31 S 32

S 6 S 5

T 27 S

1967

from which new bearing trees:

A Hemlock 16" dia., bears N.58°E., 91 lks. dist., mkd. T26S R8W S32 BT.

A Hemlock 7" dia., bears S.44°E., 31 lks. dist. mkd. T27S R8W S5 BT.

A Hemlock 6" dia., bears N.55°W., 58 lks. dist. mkd. T36S R8W S31 BT.