

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 5; & 32, T26-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - A. R. and S.C.Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 11 Page(s) 4643)

Set Fir ¼ post 3 ft. long, 3" sq., from which
A Fir 42" dia., bears S.60°E., 23 lks. dist.
A Fir 48" dia., bears N.15°E., 5 lks. dist.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #638, surveyed May\July 1967 (DCSO records Vol. 34 Page(s) 14174)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap mkd:
T 26 S R 8 W
¼ S 32
S 5
T 27 S
1967

from which
A Hemlock 10" dia., bears N.11°E., 49 lks. dist. mkd. ¼ S32 BT.
A Hemlock 9" dia., bears S.22°E., 43 lks. dist. mkd. ¼ S5 BT.