

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5327)

Set yew post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 28, 29, 32, & 33, marked T27S S 28 on NE, R8W S 33 on SE, S 32 on SW, S 29 on NW faces, with 1 notch on S & 4 notches on E edges; from which
A hemlock, 30" dia., bears N.30°E., 5 lks., mkd: T27S R8W S28 BT.
A fir, 36" dia. bears S.46°E. 13 lks. mkd: T27S R8W S33 BT
A hemlock, 36" dia., bears S.62°W., 45 lks., mkd: T27S R8W S32 BT.
A hemlock, 12" dia., bears N.65°W., 47 lks., mkd: T27S R8W S29 BT.

Weyerhaeuser corner report, no surveyor's name or stamp, no date of visit - C.S. File 58/271-12

Per note on file:
"The attached corners were visited by Douglas Co. crews with insufficient evidence available for remonumenting the corners. Weyerhaeuser information was not based on "found" original evidence and the County crew disagreed with many of Weyerhaeuser's bearing and distance to their set monument." July 1983 V. Laugen - This information added to the corner report on 2/7/2008. DCSO
From 1" pipe: 8" hemlock N.17°E., 30.2 ft.
32" cedar S.65°E., 11.1 ft.
12" hemlock S.82½°W., 53.1 ft.
30" hemlock N.65°W., 31.0 ft.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Karen Reed - Terrie Plouff - 4/27/1982 - C.S. File 61/30-28

Found - Unrecorded 1/2"x24" IP lying on ground.
Orig. 12" now 28" hemlock stump. I cut open & find scribed "S T R" positioned: S (see detail T on report R in CS file)
Rotted remains of two stumps probably the orig. NE & SE trees. Due to their condition plus disturbance by past logging I can not determine the exact limits of either stump.
Orig. SW tree is gone.
Unrecorded 15" hemlock stump w/Weyerhaeuser "W" nail
Unrecorded 38" hemlock stump w/Weyerhaeuser "W" nail
continued next page

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set - At record bearing & dist. from fd. orig. 12" now 28" Hemlock (S.65°E., 31.0 ft.) I set a 1"x30" IP with brass cap attached mkd: "DOUGLAS COUNTY SURVEYOR T27S S29 S 28 S32 S33 R8W 1982" Rec bearing & dist. for NE BT (N.30°E., 3.3 ft.) hit decayed wood. Rec. bearing & dist. for SE BT (S.46°E., 8.6 ft.) hits decayed wood.
I place unrecorded 1/2" IP alongside brass cap.

New - "W" nail in face of 15" hemlock stump bears N.4°E., 24.9 ft. to nail.
"W" nail in face of 38" hemlock stump bears S.60°E., 10.9 ft. to nail.
"W" nail in side of orig. NW BT (28" hemlock stump) bears N.65°W., 29.9 ft.

Sketch in file.