

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5335)

Set cedar post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 4, 5, 8, & 9, marked T27S S 4 on NE, R8W S 9 on SE, S 8 on SW, S 5 on NW faces, with 5 notches on S & 4 notches on E edges; from which

- A cedar, 16" dia. bears N.16°E. 4 lks. mkd: T27S R8W S4 BT
- A cedar, 10" dia., bears S.30°E., 50 lks., mkd: T27S R8W S9 BT.
- A cedar, 14" dia., bears S.32°W., 34 lks., mkd: T27S R8W S8 BT.
- A cedar, 12" dia., bears N.62°W., 80 lks., mkd: T27S R8W S5 BT.

BLM dependent resurvey by Harvey E. Wofford & John P. Farnsworth, Cadastral Surveyors under Group # 981 & 1065, surveyed May 1979/July 1981 - (DCSO records Vol. 44 Page(s) 17047)

The cor. of secs. 4, 5, 8, and 9, determined from the remains of two original bearing trees

- A root hole, bears N.16°E.; 4 lks., alongside of which is a down and burned cedar, 16" dia., with fragmentary scribe marks visible on burned blaze.
- A root hole, bears N.62°W., 80 lks., alongside of which is a down and burned cedar, 12" dia., with axe marks visible on burned blaze.

and bearing trees mkd. by Weyerhaeuser Timber Company

- A fir, 20" dia., bears N.49¼°E., 11 lks., with a nail with "W" embossed on its head at the base. Mark this tree T27S R8W S4 BT.
- A fir, 13" dia., bears S.11¼°E., 27 lks., with a nail with "W" embossed on the head at the base. Mark this tree T27S R8W S9 BT.
- A fir, 18" dia., bears S.59¼°W., 15 lks., with a nail with "W" embossed on the head at the base. Mark this tree T27S R8W S8 BT.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T27S R8W
S 5 | S 4
S 8 | S 9

from which a new BT

- A fir, 12" dia. bears N.66°W., 55 lks. mkd: T27S R8W S5 BT