

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5338)

Set a yew post, 3 ft. long, 4" sq., 24" in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W face; from which

A fir, 36" dia., bears N.40°W., 55 lks., mkd: $\frac{1}{4}$ S BT.

A fir, 24" dia., bears S.41°E., 75 lks., mkd: $\frac{1}{4}$ S BT.

BLM dependent resurvey by Harvey E. Wofford & John P. Farnsworth, Cadastral Surveyors under Group # 981 & 1065, surveyed May 1979/July 1981 - (DCSO records Vol. 44 Page(s) 17048)

Point for the $\frac{1}{4}$ sec. cor. of secs. 4 & 5, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2 $\frac{1}{2}$ " dia., 24" in the ground with brass cap marked:

T27S R8W

$\frac{1}{4}$
S 5 | S 4
1979

from which

A fir, 9" dia., bears N.19 $\frac{1}{2}$ °E., 12 lks., mkd: $\frac{1}{4}$ S4 BT.

A fir, 9" dia., bears S.46 $\frac{1}{2}$ °W., 45 lks., mkd: $\frac{1}{4}$ S5 BT.