

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5; 32 & 33, T26-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by - A. R. and S.C.Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 11 Page(s) 4643)

Cor. to secs. 4, 5, 32 and 33, Set a Fir post, 4 ft. long, 4" sq., from which
A Fir 84" dia., bears N.60°E., 23 lks. dist.
A Hemlock 36" dia., bears N.45°W., 32 lks. dist.
A Fir 40" dia., bears S.15°W., 10 lks. dist.
A Fir 60" dia., bears S.85°E., 81 lks. dist.

GLO survey by William P. Heyden, Deputy Surveyor, under contract #656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5336 and 5337 and Page #4718)

(Page 5336)
Could find no trace of old cor. to secs. 4, 5, 32 and 33, it having been destroyed by fire.
(Page 5337)
Set cor. for secs. 4, 5, 32 and 33, to wit. A Fir post 3 ft. long, 4" sq., 24" in the ground mkd. T26S S33 on NE.; R8W S4 on SE.; T27S S5 on SW.; R8W S32 on NW. faces, with 4 notches on E. and 2 notches on W. edges; from which
A Fir 30" dia., bears N.2°E., 48 lks. dist. mk.d T26S R8W S33 BT.
A Fir 30" dia., bears S.38°E, 215 lks. dist. mkd. T27S R8W S4 BT.
A Fir 36" dia., bears S.61°W., 315 lks. dist. mkd. T27S R8W S5 BT.
Tree being out of prescribed limit. Dug pit 18x18x12 ins. in sec. 5, 5½ ft. from cor.
A Fir 36" dia., bears N.28°W., 191 lks. dist. mkd. T26S R8W S32 BT.

(Page 4718)
I now return to the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp. which is a post marked as reported by the Examiner. I supply the omitted markings to wit: T26S on NE.; R8W on SE.; and T27S on SW. faces, with 4 notches on E. and 2 notches on W. edges, and dug pit 18x18x12 ins., 5½ ft. dist. SW. of cor.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #638, surveyed May\July 1967 (DCSO records Vol. 34 Page(s) 14173-74)

The Sec. cor., determined at record distance from the remaining bearing trees mkd. by Heydon:
(Cont. Next Page)

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5; 32 & 33, T26-8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A rotted Fir stump 30" dia., bears N.20°E., 48 lks. dist., with old axe marks visible on decayed blaze. (Rec. N.2°E.)
A Fir snag 45" dia., bears S.38°E., 215 lks. dist. with fragmentary scribe marks visible on decayed blaze.
A Fir snag 50" dia., bears S.61°W., 315 lks. dist., with no marks remaining.
and trees for which I have no record
A Fir 60" dia., bears N.10°E., 225 lks. dist., with scribe marks S33 T26 R8W visible on weathered bark blaze.
A Fir 52" dia., bears S.84°W., 291 lks. dist., with scribe marks T27S R8W visible on weathered bark blaze.
At the corner point
Set an iron post 28" long, 2½" dia., 25" in the ground, with brass cap mkd. T 26 S R 8 W
 S 32 S 33
 S 5 S 4
 T 27 S
 1967
from which new bearing trees
A Fir 12" dia., bears N.38°E., 21 lks. dist. mkd. T26S R8W S33 BT.
A Fir 13" dia., bears S.23°E., 21 lks. dist. mkd. T27S R8W S4 BT.
A Fir 15" dia., bears S.76°W., 24 lks. dist. mkd. T27S R8W S5 BT.
A Fir 18" dia., bears N.38°W., 12 lks. dist. mkd. T26S R8W S32 BT.

Fd. and used in BLM resurvey by Wofford and Farnsworth, Cadastral Surveyors, under Group #'s 981 & 1065, Surveyed May 1979/July 1981 - (DCSO records Vol. 44 Page(s) 17043-44)