

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5330)

-----  
Set fir post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N face; from which  
A maple, 12" dia., bears N.60°W., 74 lks., mkd: ¼ S BT.  
A fir, 18" dia., bears S.32°W., 65 lks., mkd: ¼ S BT.

Weyerhaeuser corner report, no surveyor's name or stamp, no date of visit - C.S. File 58/271-6

-----  
Per note on file: "The attached corners were visited by Douglas Co. crews with insufficient evidence available for remonumenting the corners. Weyerhaeuser information was not based on "found" original evidence and the County crew disagreed with many of Weyerhaeuser's bearing and distance to their set monument." July 1983 V. Laugen - This information added to the corner report on 2/7/2008. DCSO  
From pipe: 32" Fir S.32°W., 44.0 ft.  
12" maple N.60°W., 48.8 ft.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - John Powell - 5/3/1982 - C.S. File 61/36-2

-----  
Found - Unrecorded ¾" IP firmly set protruding 13" out of ground. From Which:  
Orig. 18" now 30" fir stump with good scar bears S.32°W., 44.4 ft. (Rec. 42.9 ft.)  
Orig. 12" maple stump, rotted and broken apart with possible reverse scribed "B" showing inside stump bears N.60°W., 48.7 ft.  
Set - Since the found ¾" IP did not fit the fir BT well for dist. & since the maple BT is just below an old cat road and looks like it could possibly have been pushed over or slid over due to the road work, I SET a 1"x30" IP with brass cap attached at record bearing & dist. from fir BT (N.32°E., 42.9 ft.) This position also fits the maple BT fairly well. (N.58°W., 48.7 ft.) (rec. N.60°W., 48.7 ft.) Cap is mkd: "Douglas Co. Surveyor T27S 1/4 S21 S28 R8W 1982"  
I leave the found 3/4" IP in the position I found it. (N.32°E., 1.6 ft. from set brass cap.)  
New - "W" nail in face of 30" fir stump (orig. BT) bears S.32°W., 41.6 ft  
"W" nail in face of 17" hemlock stump bears N.6°W., 13.8 ft.  
continued next page

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

"PK" nail in top of 15" hemlock stump bears N.89°W.,  
7.0 ft.  
Sketch of accessories in C.S. file.