

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William P. Heydon, Deputy Surveyor, under contract No 656 dated May 21 1896 - (DCSO rec Vol 13 Pg 5332)

Set cedar post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N face; from which
 A cedar, 10" dia., bears N.78°W., 54 lks., mkd: ¼ S BT.
 A cedar, 15" dia., bears S.67°W., 54 lks., mkd: ¼ S BT.

Weyerhaeuser corner report, no surveyor's name or stamp, no date of visit - C.S. File 58/271-6

Per note on file: "The attached corners were visited by Douglas Co. crews with insufficient evidence available for remonumenting the corners. Weyerhaeuser information was not based on "found" original evidence and the County crew disagreed with many of Weyerhaeuser's bearing and distance to their set monument." July 1983 V. Laugen - This information added to the corner report on 2/7/2008. DCSO
From Wood stake: 40" Fir N.06½°E., 13.4 ft
 8" hemlock S.46½°W., 35.0 ft.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - John Powell - Terrie Plouff - 5/13/1982 - C.S. File 61/36-10

Found - Orig. 10" now 15" standing, dead cedar with rotted out faces in unhealed double blaze.
 Orig. 15" now 17" cedar windfall with rotted out faces in unhealed double blaze.
Set - Using the record distances from the two orig. BTs, I SET a 1"x30" IP with brass cap attached marked "Douglas Co. Surveyor T27S ¼ S16 S21 R8W 1982", approx. 12" into the ground and then place pile of rock around IP.
Bearings and distances used are as follows:
 10" now 15" cedar bears N.77°W., 35.6 ft. (Rec. N.78°W.)
 Stump hole from 15" now 17" cedar hears S.54°W., 35.6 ft. (Rec. S.67°W.)
New BTs- 9" hemlock w/"W" nail in face scribed "¼ S21 CS BT" in double blaze bears S.45°W., 33.7 ft. to nail
 10" hemlock scribed "¼ S21 CS BT" in double blaze bears S.8½°W., 11.9 ft.
 48" fir with "W" nail in face bears N.10°E., 11.8 ft. to nail.
 10" hemlock scribed "¼ S16 CS BT" in double blaze bears N.53°E., 21.8 ft.