

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5336)

Set a yew post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N face; from which
A hemlock, 24" dia., bears N.40½°W., 27 lks., mkd: ¼ S BT.
A hemlock, 16" dia., bears S.44°W., 32 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John Powell - 10/21/1970 - C.S. File 54/119-5

Reported as not found.
From approx sec. cor. Run west between 4/9 with no results.
Area badly burnt.

BLM dependent resurvey by Harvey E. Wofford & John P. Farnsworth, Cadastral Surveyors under Group # 981 & 1065, surveyed May 1979/July 1981 - (DCSO records Vol. 44 Page(s) 17046)

Point for the ¼ sec. cor. of secs. 4 & 9, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked:

T27S R8W
¼ $\frac{S \ 4}{S \ 9}$
1979

from which
A fir, 17" dia., bears N.27¼°W., 25 lks., mkd: ¼ S4 BT.
A fir, 13" dia., bears S.49¾°E., 43 lks., mkd: ¼ S9 BT.