

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5317)

Set a fir post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 27, 28, 33, & 34, marked T27S S 27 on NE, R8W S 34 on SE, S 33 on SW, S 28 on NW faces, with 1 notch on S & 3 notches on E edges; from which

- A fir, 18" dia., bears N.82°E., 170 lks., mkd: T27S R8W S27 BT.
- A fir, 18" dia., bears S.65°E., 124 lks., mkd: T27S R8W S34 BT.
- A fir, 60" dia., bears S.58°W., 138 lks., mkd: T27S R8W S33 BT.
- A fir, 48" dia., bears N.28°W., 160 lks., mkd: T27S R8W S28 BT.

Craig Templin, LS 938 - For: Weyerhaeuser Co. Jan. 16, 1973 - C.S. File 58/271-3

Found - 60" fir, Orig. BT, now rotted snag, scribing visible bears S.58°W., 138 lks.
18" fir, OBT, windthrown, face evident bears N.82°E., 170 lks.

Set - 2" I.P. with brass cap marked "T27S R8W 28 27 33 34 1972".

New BTs- 4" incense cedar bears N.22°W., 13.1 ft.
6" chinquapin bears N.42°E., 27.3 ft.
8" fir bears S.66°W., 27.9 ft.
4" fir bears S.43°E., 14.4 ft.

All BTs marked "S T27S R8W BT". Placed Weyco tags and "W" nails on all new BTs.