

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5320)

-----  
Set a fir post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 15, 16, 21, & 22, marked T27S S 15 on NE, R8W S 22 on SE, S 21 on SW, S 16 on NW faces, with 3 notches on S & E edges; from which  
A cedar, 18" dia., bears N.31°E., 31 lks., mkd: T27S R8W S15 BT.  
A cedar, 16" dia., bears S.81°E., 16 lks., mkd: T27S R8W S22 BT.  
A madrone, 6" dia., bears S.56°W., 40 lks., mkd: T27S R8W S21 BT.  
A fir, 20" dia., bears N.48°W., 38 lks., mkd: T27S R8W S16 BT.

Weyerhaeuser corner report, no surveyor's name or stamp, no date of visit - C.S. File 58/271-6

-----  
Per note on file:  
"The attached corners were visited by Douglas Co. crews with insufficient evidence available for remonumenting the corners. Weyerhaeuser information was not based on "found" original evidence and the County crew disagreed with many of Weyerhaeuser's bearing and distance to their set monument." July 1983 V. Laugen - This information added to the corner report on 2/7/2008. DCSO  
From pipe: 18" cedar N.31°E., 20.4 ft.  
16" cedar S.81°E., 10.5 ft.  
22" madrone S.56°W., 26.4 ft.  
30" fir N.48°W., 25.1 ft.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - John Powell - Terrie Plouff - May 12, 1982 - C.S. File 61/36-9

-----  
Found - Unrecorded 3/4" IP firmly set protruding 10" out of ground.  
Orig. 18" cedar, now 24" stump with scribed "BT" visible in partially healed blaze.  
Stump hole from orig. 16" cedar, rotted remains of tree lies downhill approx. 10 ft. from hole. An old tag is still on tree but no face visible.  
Orig. 20" fir, now 25" stump shows good scar.  
Orig. 6" madrone is completely gone.  
Set - Using the three orig. BTs fd, I SET a 1"x30" IP with brass cap attached marked "Douglas County Surveyor T27S S16 S15 S21 S22 R8W 1982". cont.

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Bearings and distances used are as follows:

Orig. 18" now 24" cedar stump bears N.31°E., 20.5 ft.

Orig. 16" cedar now stump hole bears S.81°E., 10.6 ft.

Orig. 20" now 25" fir stump bears N.52°W., 25.1 ft.  
(rec.N.48°W.)

Fd ¾" I.P. bears S.46°W., 1.2 ft.

New - Spike in top of 36" cedar stump bears S.43°E., 5.4 ft.  
to spike.

Spike in top of 38" fir stump bears S.28½°W., 50.1 ft.  
to spike.

Spike in top of orig. 18" now 24" cedar stump bears  
N.31°E., 20.5' to spike.

Spike in top of orig. 20" now 25" fir stump bears  
N.52°W., 23.9 ft. to spike.