

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5324)

Set cedar post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on W face; from which
A fir, 40" dia., bears N.42°E., 72 lks., mkd: ¼ S BT.
A fir, 48" dia., bears N.80°30'W., 48 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Willie Penley - J. Heritage - 10/13/1970 - C.S. File 54/119-1

Found - 40" D.Fir, now stump N.42°E., 42.5 ft. opened for scribe "B" on burnt face.
No trace of NW BT
Set - Brass cap at cor. mkd: County Surveyors T27S R8W Office 1970 ¼ S 9|S 10
New BTs- 8" Tan Oak N.3°E., 35.0. ft. scribed ¼ S10 CS BT.
8' Hemlock S.88°W., 36.0 ft. scribed ¼ S9 CS BT.

BLM dependent resurvey by Harvey E. Wofford & John P. Farnsworth, Cadastral Surveyors under Group # 981 & 1065, surveyed May 1979/July 1981 - (DCSO records Vol. 44 Page(s) 17045-6)

The ¼ sec. cor. of secs. 9 & 10, perpetuated & recorded by Powell in 1970, monumented with an iron post, 1" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.
from which the remains of an orig. BT
A fir stump, 42" dia., bears N.42°E., 72 lks., with fragmentary scribe marks visible on an open blaze.
and BTs mkd by Powell
A tan oak, 10" dia., bears N.3°E., 52 lks., with healed blaze.
A hemlock, 11" dia., bears S.88°W., 54 lks., with healed blaze.