

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 446100

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. Sec. 34 only, T27½-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Resurvey by C. Albert White; John M. Jelley; James E. Jelley, Cadastral Surveyors, Under group #466, Surveyed Sept/Oct. 1961 - (DCSO records Vol. 30 Page(s) 12871-72)

Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

¼ S 34
T 27½ S R 8 W
1961

from which

A Fir 26" dia., bears S.61½°E., 71 lks. dist. mkd. ¼ S34 BT.

A Fir 28" dia., bears S.75°W., 79 lks. dist. mkd. X only at breast height.

(From this point the standard ¼ sec. cor. of sec. 34, T27S R8W bears N.89°12'W., 5.81 chs. dist.)

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Mike Koch - Nov. 7, 2018 (Filed 11/17/2021) - C.S. File 67/50-4

Found - A 2½" dia. Iron Pipe with a 3¼" BLM brass cap firmly set and projecting 3" (properly) marked

BTs by White (BLM 1961) -

A 24"x6' D.Fir stump bears S.62°E., 46.86 ft. (Metal Capped)

A 30"x5' D.Fir stump bears S.77°W. 52.14 ft. (Metal Capped)

North ¼ corner Sec. 3, T28S R8W is South 44.22 ft

New - A 10" D.Fir bears N.83°W., 10.6 ft. scribed "¼ S 34", "CSBT"

Note - All BTs have BT tags attached. All new BTs have double blazed faces with bearings measured to the center of the tree at the root crown and distances measured to the side and center of the root crown to a magnetic PK nail. All new BTs measured to side center root crown marked with a 2½" PK nail and double blazed. Corner is located on a steep slope approximately 260 ft. North of logging access road.

Compass declination - 15°E.