

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5308-9)

-----

Falls on rock in place, flat smooth surface, about ¼ acre in extent. I cut a cross (X) at exact cor. point for secs. 22, 23, 26, & 27, mkd with 2 notches on S & E edges; from which

- A fir, 18" dia., bears N.58°E., 200 lks., mkd: T27S R8W S23 BT.
- A fir, 48" dia. bears S.23°E. 77 lks. mkd: T27S R8W S26 BT
- A hemlock, 18" dia., bears S.81°W., 47 lks., mkd: T27S R8W S27 BT.
- A fir, 6" dia. bears N.47°W., 55 lks. mkd: T27S R8W S22 BT

-----

Weyerhaeuser corner report, no surveyor's name or stamp, no date of visit - C.S. File 58/271-7

-----

Per note on file: "The attached corners were visited by Douglas Co. crews with insufficient evidence available for remonumenting the corners. Weyerhaeuser information was not based on "found" original evidence and the County crew disagreed with many of Weyerhaeuser's bearing and distance to their set monument." July 1983 V. Laugen

Pipe from which

- 18" fir stump N.87°E., 20.1 ft.
- 60" fir S.48°W., 29.8 ft.
- 60" fir stump N.47°W., 36.3 ft.

-----

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - John Powell - May 4, 1982 - C.S. File 61/36-3

-----

Found - Unrecorded 3/4" I.P. firmly set protruding 6" out of ground.

- Orig. "X" on rock appears to be buried by 4ft-6ft of dirt & slash from old logging.
- Orig. 48" fir now 56" stump with good scar. I open blaze & find scribed "S 1" on a burned over face. The other 3 orig. BTs are gone.

Set - Since the found unrecorded 3/4" I.P. does not fit the orig. BT at all, I SET the sec. cor. at record bearing and distance from original SE BT (N.23°W., 50.1 ft.) Corner falls on large root from big fir stump & root wad buried by old logging activity. I therefore set a 5/8"x15" IR with alum, cap in said root mkd. "Douglas Co. Sec Cor 1982 Surveyor".

Found 3/4" I.P. bears N.20°W., 32.7 ft. from set 5/8" I.R. continued next page

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - 23" cedar scribed "T27S R8W S27 CS BT" in double  
blaze bears S.47°W., 32.8 ft.  
"PK" nail in top of 60" fir stump bears N.79°W.,  
33.7 ft. to nail.  
Corner lies approx 200 ft. below road on a very steep rock  
slope.