

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5311-2)

-----

Set a yew post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on W face; from which  
A hemlock, 12" dia., bears N.31°E., 16 lks., mkd: ¼ S BT.  
A fir, 6" dia., bears N.54°W., 45 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - John Powell - June 3, 1982 - C.S. File 61/36-20

-----

Found - Unrecorded 3/4" I.P. firmly set protruding 7" out of ground. From Which:  
Orig. 12" hemlock, now 18" stump, previously opened showing scribe "1/4 S" bears N.31°E., 10.6 ft.  
Orig. 6" fir now 76" stump, (it would appear orig. notes should have said 60" fir) bears N.54°W., 29.7 ft. to face. The stump is cut fairly low and does not show face.

Set - At the location of the found 3/4" I.P. I SET a 1"x 30" I.P. with brass cap attached protruding 9" out of ground. I place found I.P. along north edge of brass cap. Cap marked "Douglas Co Surveyor T27S S15 S14 ¼ R8W 1982".

New - Spike stamped "B01" set in top of 76" fir stump bears N.54°W., 31.6'  
Spike stamped "B02" set in top of 35" hemlock stump bears S.10°E., 34.9 ft.  
W nail fd. in face of 20" hemlock stump bears N.76½°W., 3.0 ft.