

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5312)

-----

Set a cedar post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 10, 11, 14, & 15, marked T27S S 11 on NE, R8W S 14 on SE, S 15 on SW, S 10 on NW faces, with 4 notches on S & 2 notches on E edges; from which

A fir, 30" dia. bears N.16°E. 83 lks. mkd: T27S R8W S11 BT

A hemlock, 28" dia., bears S.20°E., 30 lks., mkd: T27S R8W S14 BT.

A hemlock, 14" dia., bears S.58°W., 14 lks., mkd: T27S R8W S15 BT.

A fir, 40" dia. bears N.22°W. 88 lks. mkd: T27S R8W S10 BT

Romanso E. Ware - For: Revestco - June 1979 - M77-69

-----

Found - Unrecorded Weyerhaeuser corner and BTs.

Set - 5/8" Iron rod

BTs - 14" Fir bears N.80°W., 9.5 ft scribed "T27S R8W S10 BT".

18" Fir bears N.40°E., 5.5 ft. scribed "T27S R8W S11 BT"

18" Fir bears S.32°E., 18.5 ft. scribed "T27S R8W S14 BT"

12" Fir bears S.42°W., 17.8 ft. scribed "T27S R8W S15 BT"