

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor Secs 2, 3, 10, & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5314)

-----  
Set a yew post, 50 ft. below ridge, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 2, 3, 10, & 11, marked T27S S 2 on NE, R8W S 11 on SE, S 10 on SW, S 3 on NW faces, with 5 notches on S & 2 notches on E edges; from which  
A fir, 40" dia. bears N.43°E., 45 lks. mkd: T27S R8W S2 BT  
A fir, 40" dia. bears S.66°E. 84 lks. mkd: T27S R8W S11 BT  
A cedar, 4" dia., bears S.33°W., 113 lks., mkd: T27S R8W S10 BT.  
A fir, 40" dia. bears N.39°W. 120 lks. mkd: T27S R8W S3 BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - C. Putnam - Aug. 14, 1959 - C.S. File 49/79-43

-----  
Found - Orig. 40", now 48" Fir N.43°E. 29.7 ft., previously opened, shows good scribing "2 S".  
Orig. 4", now 36" Cedar S.33°W. 74.6 ft., shows good scars. I do not open.  
Orig. 40", now 44" Fir Snag shows good scar, S.66°E. 55.4 ft.  
Orig. 40", now 48" Fir N.39°W. 79.2 ft., shows good scars.

Set Brass Cap at Corner mkd: County Surveyor's Office, 1959

S 3   S 2	T27S R8W
S 10   S 11	

New BTs- 7" R.Fir bears S.71½°E., 36.5 ft. scribed S11 T27S R8W CS BT  
9" R.Fir bears N.36½°W. 34.4 ft. scribed S 3 T27S R8W CS BT

FD. Ok by JMP (DCSO) Oct. 1970, C.S. File 54/119-2

Fd. BC & 4 BTs - Craig L. Templin - March 22, 1973 - C.S. File 55/285C

BLM dependent resurvey by Harvey E. Wofford & John P. Farnsworth, Cadastral Surveyors under Group # 981 & 1065, surveyed May 1979/July 1981 - (DCSO rec. Vol. 44 Page 17045)

-----  
The cor. of secs 2, 3, 10, & 11, perpetuated & recorded by Byron, in 1959, monumented w/an iron post 1" dia., firmly set, projecting 6" above ground with brass cap (properly) mkd from which the remains of the Orig. BTs

continued next page

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 50" dia., bears N.43°E., 45 lks., with scribe marks  
8W BT visible on open blaze.  
A fir snag, 44" dia., bears S.66°E., 84 lks., with healed  
blaze.  
A cedar stump, 36" dia., bears S.33°W., 113 lks., no marks  
visible.  
A fir stump, 48" dia., bears N.39°W., 120 lks., no marks  
visible.  
and BTs mkd. by Byron  
A fir, 12" dia., bears S.71½°W., 51 lks., no marks visible  
A fir stump, 10" dia., bears N.36½°W., 51 lks., no marks  
visible.  
Per BLM plat:           Latitude       43°14.6'N  
                                  Longitude     123°37.4'W