

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5315-6)

Set yew post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on W face; from which
 A fir, 48" dia., bears S.52°W., 50 lks., mkd: ¼ S BT.
 A fir, 40" dia., bears S.47°E., 60 lks., mkd: ¼ S BT.

Craig L. Templin - For: Weyerhaeuser Co. - March 22, 1973 - C.S. File 55/285C

Set - 2" Pipe with a Brass Cap, from which:
 26" Fir bears S.56°W., 17.5 ft. (Weyco tag & "W" nail)
 26" Fir bears S.78°E. 34.3 ft. (Weyco tag & "W" nail)
Distances are horizontal distances to the center of the tree & bearings were taken on the "W" nail in the base of each tree. Lines were blazed and marked with 2"x8" aluminum tag nailed to trees on the property adjoining Weyerhaeuser Co. and by red and white striped engineer's flagging on the prop. line.

Fd. Ok by Ken Hoffine - 2/1994 - M118-46