

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heyden, Deputy Surveyor, under contract #656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5278-79)

-----  
Set W.C. to  $\frac{1}{4}$  S. C., 1 chain North of point for true cor. which is on face of steep rocky ledge. A Fir post 3 ft. long, 4" sq.; on bed rock in stone mound  $2\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, mkd. W C S C  $\frac{1}{4}$  S on N. face, from which  
A Fir 18" dia., bears N.83°E., 45 lks. dist., mkd. W C S C  $\frac{1}{4}$  S BT.  
A Fir 24" dia., bears N.53°W., 50 lks. dist. mkd. W C S C  $\frac{1}{4}$  S BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - April 24, 1970 - C.S. File 54/113-8

-----  
Looked for, not found.  
Cor. lies at top of high bluff, being a wit. cor. All timber to the south has been cut and burnt. Wit. Cor. on top of bluffs not found, may have washed out or been burnt.