

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5309)

-----  
Set yew post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., 100 ft. above Lost Creek, marked ¼ S on N face; from which  
A fir, 30" dia., bears N.48°W., 4 lks., mkd: ¼ S BT.  
A fir, 28" dia., bears S.62°W., 28 lks., mkd: ¼ S BT.

-----  
Weyerhaeuser corner report, no surveyor's name or stamp, no date of visit - C.S. File 58/271-7 & 10

-----  
Per note on file:  
"The attached corners were visited by Douglas Co. crews with insufficient evidence available for remonumenting the corners. Weyerhaeuser information was not based on "found" original evidence and the County crew disagreed with many of Weyerhaeuser's bearing and distance to their set monument." July 1983 V. Laugen - This information added to the corner report on 2/5/2008. DCSO  
There are 2 sheets on this corner & they don't agree:  
C.S. 58/271-7 -  
3/4" IP from which  
32" Fir stump N.27°E., 27.5 ft.  
36" fir stump S.62°W., 15.9 ft.  
C.S. 58/271-10  
1" IP from which  
18" Fir N.30°E., 51.8 ft.  
8" Fir S.21½°E., 37.7 ft.

-----  
Douglas Co. Surveyors Office - Gregory Quibell, Deputy - John Powell - May 6, 1982 - C.S. file 61/36-4

-----  
Found - Unrecorded 3/4" I.P. firmly set protruding 10" out of ground.  
Orig. 28" fir now 33" stump with pitched over previously opened face "W" nail in edge of face. I open more of face and find scribed "BT" ("BT" is upside down) visible under layer of pitch.  
Orig. 30" fir BT appears to be destroyed by logging.  
Set - At rec. bearing & dist. from orig. 28" now 33" fir stump (N.62°E., 18.5 ft.) I SET a 1" x 30" I.P. with brass cap attached marked: "Douglas Co. Surveyor "T27S ¼ S23 S26 R8W 1982".  
Found 3/4" I.P. bears N.83°W., 1.6 ft. I do not disturb 3/4" I.P.  
continued next page

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - Set spike in top of 36" fir stump bears N.23°E.,  
27.7 ft. Spike is stamped "BO"

1

Set spike in top of 30" fir stump bears S.5½°E., 7.2  
ft. Spike is stamped "BO"

2

Sketch of accessories in C.S file.