

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias	Description

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5297)

Set a yew post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor 200 ft above creek marked ¼ S on W face; from which
A fir, 30" dia., bears N.40°E., 15 lks., mkd: ¼ S BT.
A fir, 30" dia., bears S.44°W., 60 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - John Powell - Terrie Plouff - May 12-18, 1982 - C.S. File 61/36-12

Found - Unrecorded 1¼" I.P. protruding 8" out of ground. Orig. 30" now 40" fir stump with well healed over double blaze.

Unrecorded 33" fir stump with healed up scar, I opened and found ¼S BT in double blaze. Orig. SW fir BT is completely gone.

Set - Using record bearing & distance from orig. 30" now 40" fir BT (S.40°W., 9.9 ft.) I SET a 1"x30" I.P. with brass cap attached marked "Douglas Co. Surveyor T27S S26 S25 ¼ R8W 1982". Brass cap protrudes 9" out of ground.

Unrecorded 1¼" I.P. bears S.40°W., 1.65 ft. (appears to have been set by measuring from face of fir BT)

New BTs- 7" Chinquapin scribed "¼ S25 CS BT" in double blaze bears S.60°E., 13.6 ft.

17" cedar stump with nail in face and L in bark bears S.75°E., 6.4 ft. to nail.

12" yew scribed "¼ S25 CS BT" in double blaze bears N.16°E., 44.6'

33" fir stump with found scribed "¼ S BT" bears N.44°W., 35.1 ft. to PK nail set in face.

38" fir stump with "W" nail in face bears N.71°W., 45.6 ft. to nail.

Tony Hostetter - For: Weyerhaeuser Co. - June 9, 2015 - C.S. File 65/89-54

Found - 1982 Douglas Co. Surveyor brass cap as described in C.S. File 61/36

40" Fir stump, face evident, OBT, bears N.40°E., 9.9 ft. to center.

12" Yew, face evident, BT tag, bears N.16°E., 44.6 ft. to center.

17" cedar stump, BT Tag, bears S.75°E., 6.4 ft. to nail in face. continued next page

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

33" Fir stump, scribing visible, bears N.44°W., 35.1 ft. to PK nail in face.
1¼" iron pipe bears S.40°(W) ., 1.65 ft.
New BTs- 16" fir, BT tag, bears S.08°E., 9.5 ft. to 6" spike, placed below tag.
20" fir, BT tag, bears S.58°W., 24.2 ft to 6" spike, placed below tag.
15" fir BT tag, bears N.36°W., 22.4 ft. to 6" spike, placed below tag.
16" fir BT tag, bears N.20°W., 24.2 ft. to 6" spike, placed below tag.