

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5299-5300)

Set a cedar post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 13, 14, 23, & 24, marked T27S S 13 on NE, R8W S 24 on SE, S 23 on SW, S 14 on NW faces, with 3 notches on S & 1 notch on E edges; from which
A fir, 40" dia. bears N.63°E. 35 lks. mkd: T27S R8W S13 BT
A laurel, 14" dia., bears S.65°E., 95 lks., mkd: T27S R8W S24 BT.
A fir, 14" dia. bears S.44°W. 43 lks. mkd: T27S R8W S23 BT
A fir, 26" dia., bears N.22½°W., 45 lks., mkd: T27S R8W S14 BT.

Weyerhaeuser corner report, no surveyor's name or stamp, no date of visit - C.S. File 58/271-8

Per note on file:
"The attached corners were visited by Douglas Co. crews with insufficient evidence available for remonumenting the corners. Weyerhaeuser information was not based on "found" original evidence and the County crew disagreed with many of Weyerhaeuser's bearing and distance to their set monument." July 1983 V. Laugen - DCSO
The following information is on Weyerhaeuser Co. paper:
(From Corner position): 60" Fir N.63°E., 24.0 ft.
18" G.Fir S.50°E., 21.9 ft.
?(rec. fir) S.44°W., 28.3 ft.
32" Fir N.22½°W., 30.0 ft.