

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs 1, 2, 11, & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5303)

Set yew post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 1, 2, 11, & 12, 100 ft. above creek, marked T27S S 1 on NE, R8W S 12 on SE, S 11 on SW, S 2 on NW faces, with 5 notches on S & 1 notch on E edges; from which

- A cedar, 18" dia., bears N.19°E., 67 lks., mkd: T27S R8W S1 BT.
- A hemlock, 18" dia., bears S.39°E., 47 lks., mkd: T27S R8W S12 BT.
- A yew, 8" dia., bears S.36°W., 13 lks., mkd: T27S R8W S11 BT.
- A cedar, 12" dia., bears N.66°W., 28 lks., mkd: T27S R8W S2 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - C. Putnam - Aug. 14, 1959 - C.S. File 49/79-44

Found - Orig. 18", now 36" cedar N.19°E. 44.2 ft., shows good scars, I do not open.
Orig. 8" Yew, now 10" Yew Stump, partly burned, shows good scribing "8 W" S.36°W. 8.6 ft.
No trace of Original NW or SE BTs.

Set Brass Cap at Corner Mkd: County Surveyors Office, 1959

S 2 S 1	T27S R8W
S 11 S 12	

New BTs- 8" Hemlock bears S.54°E. 12.4 ft. scribed S12 T27S R8W CS BT
10" Hemlock bears S.45°W. 3.0 ft. scribed S11 T27S R8W CS BT
8" Hemlock bears N.39°W. 16.0 ft. scribed S2 T27S R8W CS BT
Original NE BT is OK.

Fd. BC & 4 BTs, Craig L. Templin - March 22, 1973 - C.S. File 55/285C