

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5305)

Set a yew post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on W face; from which
A fir, 30" dia., bears S.22°W., 14 lks., mkd: ¼ S BT.
A fir, 20" dia., bears S.45°E., 75 lks., mkd: ¼ S BT.

Craig Templin - For: Weyerhaeuser Co. - March 22, 1973 - C.S. File 55/285C

Found the E¼ cor. sec. 2, A 2" pipe N.0°3'30"E., of the SE cor. sec. 2 from which
14" fir bears N.83°E., 18.6 ft. (Weyco tag & "W" nail)
46" fir bears S.59°W., 17.1 ft. (Weyco tag & "W" nail)

Ken Hoffine, L.S. 2291 - For: Lone Rock Timber Co. - Feb. 1994 - M 118-46

Found - 2½" Iron pipe with top etched ¼
40" Low stump bears S.20°W., 7.0'.
44" Low stump bears S.60°W., 19.5' to mid stump (rec. S59°W., 17.1' to face) WEYCO tag.
16" stump bears N.82°E., 19.5' to mid stump (rec. N.83°E., 18.6' to face), WEYCO tage and nail at base.
I tag a 5" D.Fir bearing S.31°E., 20.8'.
Corner lies on SW slope approximately 150' form the end of a dirt road.