

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William P. Heydon, Deputy Surveyor, under contract No. 656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5298-9)

Set yew post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., (elevation 50 ft. below sec. cor.) marked ¼ S on N face; from which

- A hemlock, 18" dia., bears S.28°W., 8 lks., mkd: ¼ S BT.
- A hemlock, 20" dia., bears N.43°W., 54 lks., mkd: ¼ S BT.

Weyerhaeuser corner report, no surveyor's name or stamp, no date of visit - C.S. File 58/271-8

Per note on file: "The attached corners were visited by Douglas Co. crews with insufficient evidence available for re-monumenting the corners. Weyerhaeuser information was not based on "found" original evidence and the County crew disagreed with many of Weyerhaeuser's bearing and distance to their set monument." July 1983 V. Laugen - DCSO

The following information is on Weyerhaeuser Co. paper:
(From the corner position) 24" hemlock S.28°W., 4.4 ft.
30" hemlock N.07°E., 23.0 ft.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - John Powell - May 10, 1982 - C.S. File 61/36-6

Found - Orig. 18" now 23" hemlock with "BTs visible in previously opened face. Since tree has had a lot of axe work and cruiser marks I am not sure this is orig. scribing. Therefore I open upper part of face and find scribed "1/4S".

Set - Orig. 20" hemlock has been taken out by cat trail. At record bearing & distance (N.28°E., 5.3 ft.) from orig. 18" now 23" hemlock BT, I SET a 1"x30" I.P. with brass cap attached mkd. "Douglas Co Surveyor T27S ¼ S24 S25 R8W 1982". Due to large root I could only set I.P. 8" into the ground then surround the I.P. with logs approx. 15" in diam. and then filled the center in with dirt making a mound approx. 3 ft. square and 15" deep.

New BTs- 19" hemlock scribed "¼ S25 CS BT" in double blaze, bears S.86°E., 69.6 ft.
42" hemlock scribed "¼ S24 CS BT" in double blaze, bears N.68°W., 21.7 ft.
26" hemlock with "W" nail in face which I scribe "¼ S24 CS BT" in double blaze bears N.3½°E., 22.7 ft. to nail.