

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec Cor for 24 & 25; 19 & 30, T27-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Under Contract #57 dated April 12, 1855 (DCSO records, Volume 12 Page 5227)

Set post, cor. secs. 19, 30, 24 & 25 from which,
A fir, 18" dia., bears N.31°W., 34 lks.
A fir, 5" dia., bears N.9°E., 22 lks.
A fir, 40" dia., bears S.71°E., 30 lks.
A fir, 12" dia., bears S.69°E., 25 lks.

GL0 survey by A.R. Flint and L.C. Flint, under Contract #392, dated May 26, 1881 (DCSO records, Vol. 13 Pgs. 5265-66)

Cor. to secs. 19, 30, 24 and 25 - made and set new Hemlock post, 42" long 4" sqr., from which the old witness trees:
Fir 18" dia., bears N.31°W., 34 lks. dist.
Fir 5" dia., bears N.9°E., 22 lks. dist.
Fir 40" dia., bears S.71°E., 30 lks. dist.
Fir 12" dia., bears S.69°W., 25 lks. dist.
(Could find no source reference for this description - see "old" corner book, Page 96)

Renew corner with Laurel post marked S.24 on NW., S.25 and CS on SW., S.30 on SE, and S.19 on NE. Two trees down and two standing.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam - Dec. 1960 - C.S. File 49/79-78

Found - Orig. 40" now 60" Fir S.71°E., 19.8 ft., shows good bark scribing.
Orig. 18" now 28" W.Fir N.31°W., 22.4 ft. We open & find good scribing "2".
Other BTs not found.

Set brass cap at cor. mkd: County Surveyor's

S24	S19	T27S	
R8W	S25	S30	R7W

New BTs- 18" R.Fir S.19°W., 26.7 ft. scribed S25 T27S R8W
CS BT.
8" W.Fir S.4°E., 29.9 ft. scribed S30 T27S R7W CSBT
12" W.Fir N.79°E., 29.0 ft. scribed S19 T27S R7W CS
BT.
28" W.Fir N.26°W., 20.6 ft. scribed S24 T27S R8W CS
BT.

continued next page

TOWNSHIP 27 RANGE 08 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec Cor for 24 & 25; 19 & 30, T27-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Weyerhaeuser corner report, no surveyor's name or stamp, no date of visit - C.S. File 58/271-8

Per note on file:

"The attached corners were visited by Douglas Co. crews with insufficient evidence available for remonumenting the corners. Weyerhaeuser information was not based on "found" original evidence and the County crew disagreed with many of Weyerhaeuser's bearing and distance to their set monument."

July 1983 V. Laugen - DCSO

The following information is on Weyerhaeuser Co. paper:

From pipe:

- 10" hemlock N.79°E., 29.3 ft.
- 6" hemlock S.05°E., 29.7 ft.
- 12" fir S.19°W., 26.5 ft.
- 24" hemlock N.25°W., 20.8 ft.

Tony Hostetter - For: Weyerhaeuser Co. - May 2000 - M 135-4

- Found - 1½" IP/BC set by DCSO in 1958, from which
- 60" Fir stump, no marks visible, OBT bears: S.71°E., 19.8 ft.
 - 28" Fir stump, OBT, scribing visible, bears N.31°W., 22.4 ft.
 - 20" Fir stump 8' tall stump w/face evident, bears S.19°W., 26.7 ft.
- New BTs-
- 6" Fir scribed "S19 SW BT" bears N.33°E., 22.9 ft. to 6" spike in root collars, below face. BT tag.
 - 8" Fir scribed "S30 NW BT" bears S.40°E., 6.3 ft. to 6" spike in root collars below face. BT tag.
 - 8" Fir scribed "S25 NE BT" bears S.80°W., 8.1 ft. to 6" spike in root collars, below face. BT tag.

Found OK by T. Hostetter, July 2001 - M138-66