

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. Sec. 32 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Resurvey by C. Albert White; John M. Jelley; James E. Jelley, Cadastral Surveyors, Under group #466, Surveyed Sept/Oct. 1961 - (DCSO records Vol. 30 Page(s) 12873)

Set an iron post 28" long, 2½" dia., 24" in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

¼ S 32
T 27½ S R 8 W
1961

from which

A Cedar 22" dia., bears S.72½°E., 46 lks. mkd. ¼ S32 BT.

A Hemlock 40" dia., bears S.36°W., 107 lks. mkd. ¼ S32 BT.

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - April 18, 1973 - C.S. File 55/286

Found - 1961 Cadastral brass cap.

Orig. Cedar 22" dia., S.72½°E., 46 lks., scribe visible but now a shattered stump.

Orig. Hemlock 40" dia., S.36°W., 107 lks., scribe not visible now a stump.

New BT - Scribed 6" dia. Yew S.41°E., 17.7 ft. "¼ S 32 BT"

All of section 32 has been clear cut. There are no other trees suitable for bearing trees.

Douglas County Surveyors Office - R.B. Kimberling; S.J. Flause, crew - Dec. 5, 1977 - C.S. File 59/42-21

Found - 2½" Iron pipe with brass cap mkd. in 1961.

A stump hole bears S.72½°E., 30.4 ft. Remains of tree not found.

A 40" Hemlock stump bears S.36°W., 70.6 ft. with no visible blaze.

A 6" now 8" Yew bears S.36°E., (Rec. S.41°E.) 17.7 ft. scribing "¼ S32 BT" visible on partially healed blaze.

Stamped "N" on brass cap to read "N 1/4 S32 T27½S R8W 1961".

Tony Hostetter - For: Weyerhaeuser - Feb. 2005 (added 7/31/2019) - M147-36

Found - 1961 BLM brass cap from which:

12" Yew, BLM tag, scribing visible, bears S.41°E., 17.7 ft.

New BTs- 18" Fir, scribed "S32 ¼ BT", bears S.86°E, 21.7 to spike.

Continued next page

TOWNSHIP 27½ RANGE 08 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. Sec. 32 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

12" Hemlock, scribed "S32 ¼ BT", bears N.82°19'W.,
4.2 ft. to spike.
BTs measured to 6" spikes placed in root collar below face.