

TOWNSHIP 27½ RANGE 08 POINT IDENTIFIER # 334200

PRIMARY CORNER DESCRIPTION Standard ¼ sec. cor. 33 only, T27-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heyden, Deputy Surveyor, under contract #656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5281)

Set a Yew post 3 ft. long. 4" sq., 24" in the ground for standard ¼ sec. cor., marked S C ¼ S on N. face, from which
A Fir 16" dia., bears N.17°W., 43 lks. dist. mkd. S C ¼ S BT.
A Fir 20" dia., bears N.63°E., 37 lks. dist. mkd. S C ¼ S BT.

BLM Resurvey by C. Albert White; John M. Jelley; James E. Jelley, Cadastral Surveyors, Under group #466, Surveyed Sept/Oct. 1961 - (DCSO records Vol. 30 Page(s) 12869)

The standard ¼ sec. cor., determined at record distance from each of the original bearing trees:

A Fir 38" dia., bears N.54°E., 37 lks. dist. mkd. with a bark scribed S, (original) and a local cruiser mark. (Rec. brg. N.63°E.) Add the marks ¼ S33 SC BT on a new blaze.

A rotted Fir stump 18" dia., bears N.17°W., 43 lks. dist. mkd. ¼ S on the remains of a rotted face.

and a bearing tree mkd. by Weyerhaeuser Timber Company:

A Fir 35" dia., bears N.33°W., 57 lks. dist. mkd. with a spike driven into a small blaze at the root crown.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

S C
T 27 S R 8 W
¼ S 33
1961

from which a new bearing tree:

A Hemlock 10" dia., bears N.50½°W., 60 lks. dist. mkd. ¼ S33 SC BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew May 18, 1970 - C.S. File 54/113-16

Found - 1961 Cadastral brass cap, out of place, approx. 2.0 ft. and buried 2 ft. deep.

Orig. 38" Fir, alive, N.54°E., 24.4 ft. Rescribe visible on unhealed blaze.

1961 10" now 12" Hemlock, alive, N.50½°W., 39.6 ft., scribe visible on nearly healed blaze.

No trace other bearing trees called for due to logging.

(Cont. Next Page)

TOWNSHIP 27½ RANGE 08 POINT IDENTIFIER # 334200

PRIMARY CORNER DESCRIPTION Standard ¼ sec. cor. 33 only, T27-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

RESET CADASTRAL BRASS CAP at corner point.
New BT - 9" Hemlock N.39°E., 13.5 ft. mkd. ¼ S33 SC CS BT.