

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5784)

Marked a Fir 4" dia. for ¼ sec. cor., from which
A Fir 10" dia., bears S.25°E., 20 lks.
A Fir 4" dia., bears N.30°E., 3 lks.

BLM Resurvey by C. Albert White; John M. Jelley; James E. Jelley, Cadastral Surveyors, Under group #466, Surveyed Sept/Oct. 1961 - (DCSO records Vol. 30 Page(s) 12861-62)

The standard ¼ sec. cor. of sec. 4, determined at record bearing and distance from the original SE. bearing tree:

A Fir 25" dia., bears S.25°E., 20 lks. dist., mkd. with an opened blaze, illegible bark scribing and Lecklider's cruiser mark. Reblaze and mark ¼ S4 SC BT.

A piece of Fir pitch face, 3" wide, 18" long, mkd. BT, was found lying beside the corner point. Lecklider asserts that this is the remainder of the original NE. bearing tree.

and a tree mkd. by Boyer, RPE 1581:

A Hemlock 10" dia., bears N.67°W., 20 lks. dist., mkd. ¼ S4 and other illegible scribe marks on a partially overgrown face.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

¼ S 4
T 28 S R 8 W
S C
1961

from which a new bearing tree:

A Hemlock 6" dia., bears S.38°W., 35 lks. dist. mkd. ¼ S4 SC BT.

Douglas Co. Surveyors Office - V.R. Tracy, and crew - May 18, 1970 - C.S. File 54/113-15

Found - 1961 BLM brass cap, properly set and marked.
Orig. 25" Fir, alive, S.25°E., 13.2 ft., rescribe visible on unhealed blaze.
10" Hemlock N.67°W., 13.2 ft., blazes nearly healed.
We tag. (Boyer's BT)
6" Hemlock broken off 15 ft. high, dying, S.38°W., 23.1 ft. scribe visible.

(Cont. Next Page)

TOWNSHIP 27½ RANGE 08 POINT IDENTIFIER # 339100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 4, T28-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BT - 7" Hemlock S.44°W., 20.8 ft. mkd. ¼ S4 SC CS BT.
Corner lies on top of spur, sloping W.
The ¼ cor. of sec. 33, T27½-8, bears N.89½°E., 27.1 ft.

Fd. OK Dec. 1996 by R. Hintz - M 103-8