

TOWNSHIP 27½ RANGE 08 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 33 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Resurvey by C. Albert White; John M. Jelley; James E. Jelley, Cadastral Surveyors, Under group #466, Surveyed Sept/Oct. 1961 - (DCSO records Vol. 30 Page(s) 12861)

Point for the ¼ sec. cor. of sec. 33 only, on the S. bdy. of T27½S R8W.

Set an iron post 28" long, 2½" dia., 14" in the ground, to solid rock, and in a mound of stone, 2 ft. base, to top, with brass cap mkd:

T 27½ S R 8 W
 ¼ S 33
 1961

from which

A Fir 28" dia., bears N.53½°E., 24 lks. dist. mkd. ¼ S33 BT.

An Oak 9" dia., bears N.27°W., 18 lks. dist. mkd. ¼ S33 BT.

Douglas Co. Surveyors Office - V.R. Tracy, and crew - May 18, 1970 - C.S. File 54/113-14

Found - 1961 BLM brass cap, properly mkd. and set.
9" Chinquapin, alive, N.27°W., 11.9 ft., bark scribed "¼ S33 BT" low and bark scribe "BT" 5 ft. high. (Rec. as Oak) We rescribe in wood, "¼ S33 CS BT."

No trace of NE. BT, due to cat skid trail.

New BT - 8" Hemlock N.68°E., 75.4 ft. mkd. ¼ S33 CS BT.
Corner lies on top of spur, sloping W. and the standard ¼ cor. sec. 4, T28-8, bears S.89½°W., 27.1 ft.

Fd. OK, Dec. 1986 by R. Hintz - M 103-8