

TOWNSHIP 27½ RANGE 08 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION N. 1/4 cor. for Sec. 33 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Resurvey by C. Albert White; John M. Jelley; James E. Jelley, Cadastral Surveyors, Under group #466, Surveyed Sept/Oct. 1961 - (DCSO records Vol. 30 Page(s) 12872-73)

Set an iron post 28" long, 2½" dia., 14" in the ground, to solid rock and in a mound of stone 2 ft. base, to top, with brass cap mkd.

¼ S 33
T 27½ S R 8 W
 1961

from which

 A Hemlock 6" dia., bears S.29°E., 29 lks. dist. mkd. ¼ S33 BT.

 A Hemlock 8" dia., bears S.52½°W., 31 lks. dist. mkd. X only at breast height.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
May 18, 1970 - - C.S. File 54/113-16A

Looked for, not found.

Found 1961 Cad. brass cap out of ground and carried up hill. We measure S.89½°E., 399.3 ft. from the standard ¼ cor. of sec. 33 of T27S R8W following 1961 blazed line and fall in junction of cat skid roads. From this point, we find no trace of BTs called for. We took brass cap to County Surveyors Office.