

TOWNSHIP 27½ RANGE 08 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION C.C. for Secs. 33 & 34 (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Resurvey by C. Albert White; John M. Jelley; James E. Jelley, Cadastral Surveyors, Under group #466, Surveyed Sept/Oct. 1961 - (DCSO records Vol. 30 Page(s) 12871)

Point for the closing cor. of secs. 33 and 34.
Set an iron post 28" long, 2½" dia., 21" in the ground, and in a mound of stone 3 ft. base, to top, with brass cap mkd.

T 27 S R 8 W
 S 34
 S 33 | S 34
T 27½ S | R 8 W
 C C
 1961

from which

A Fir 7 17"* dia., bears S.72½°E., 33 lks. mkd. T27½S R8W S34 CC BT.

A Fir 6 16"* dia., bears S.45°W., 17 lks. mkd. T27½S R8W S33 CC BT.

(From this point the standard cor. of secs. 33 and 34, T27S R8W bears N.88°58'W., 5.80 chs. dist.)

*V.R. Tracy fd the dia. as shown above 5/1970 C.S. 54/113-17A