

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William P. Heyden, Deputy Surveyor, under contract #656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5279-80)

-----  
Set a Yew post 3 ft. long, 4" sq., 2 ft. in stone mound with 3 ft. base and 2 ft. high for 1/4 sec. cor. (on summit of sharp ridge bearing E. and W.) marked S C 1/4 S on N. face, from which

A Fir 10" dia., bears N.70°E., 32 lks. dist. mkd. S C 1/4 S BT.

A Fir 20" dia., bears S.1°W., 37 lks. dist. mkd. SC 1/4 S BT.

The nature of surface is such as to render driving the post in the earth impracticable; hence it was planted in the stone mound.

BLM Resurvey by C. Albert White; John M. Jelley; James E. Jelley, Cadastral Surveyors, Under group #466, Surveyed Sept/Oct. 1961 - (DCSO records Vol. 30 Page(s) 12867)

-----  
The standard 1/4 sec. cor. of sec. 34, determined from the original bearing trees:

A Fir 35" dia., bears N.19°W., 32 lks. dist., mkd. with illegible scribe marks at breast height on a previously opened face and BT on opened blaze above the root crown, of proper age, facing the corner.

A Fir 40" dia., bears N.63 1/2°E., 37 lks. dist. mkd. with a very old cruiser mark in the bark, at breast height, but no legible scribe marks. Add marks 1/4 S34 SC BT in the wood.

The Heydon record calls for a Fir 10" dia., N.70°E., 32 lks. dist., and a Fir 20" dia., S.1°W., 37 lks. dist. These bearings cannot be reconciled with the conditions on the ground and the above described position was arrived at as the most logical position of the original corner.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

S C  
T 27 S R 8 W  
1/4 S 34  
1961

Douglas Co. Surveyors Office - L.E. Monrean; J.H. Cook, crew - March 2, 1976 - C.S. File 59/8

-----  
Found - A Fir 35" now 37" scribed "BT" uprooted, standing position, bears N.19°W., 21.1 ft.

(Cont. Next Page)

TOWNSHIP 27½ RANGE 08 POINT IDENTIFIER # 434200

PRIMARY CORNER DESCRIPTION Standard So. 1/4 Cor. Sec. 34, T27-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A Fir 40" now 31" scribed "¼ S34" uprooted, standing position, bears N.63½°E., 24.4 ft.  
Did not find monument set in 1961.  
Set brass cap at ¼ corner stamped: County Surveyors Office  
1976  
S C  
T 27 S R 8 W  
1/4 S 34  
New BTs- A Wester Hemlock 9", bears N.32°E., 48.6 ft., double blazed and scribed ¼ S34 CS BT.  
Fence post with witness sign, bears N.42°W., 2.8 ft.  
Did not scribe second BT as there are none accessible at this time.

See also undated WEYCO report C.S. File 58/271-14 for fd ok (added 8/3/2020)