

TOWNSHIP 27~~1/2~~ RANGE 08 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION S C for Secs. 34 & 35, T27-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William P. Heyden, Deputy Surveyor, under contract #656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5279)

Set a Yew post 3 ft. long, 4" sq., 24" in the ground for standard cor. of secs. 34 and 35, marked S C T27S R8W on N.; S35 on E.; and S34 on W. faces, from which
A Fir 36" dia., bears N.70°E., 49 lks. dist. mkd. T27S R8W S35 BT.
A Fir 40" dia., bears N.20°W., 60 lks. dist. mkd. T27S R8W S34 BT.

BLM Resurvey by C. Albert White; John M. Jelley; James E. Jelley, Cadastral Surveyors, Under group #466, Surveyed Sept/Oct. 1961 - (DCSO records Vol. 30 Page(s) 12866-67)

The standard cor. of secs. 34 and 35, determined at record bearing and distance from the original NE. bearing tree:
A Fir 54" dia., bears N.70°E., 49 lks. dist. mkd. in the bark T27S R8W S35 BT.
A Fir 60" dia., turned out and dead, bears N.20°W., 26 lks. dist. mkd. in the bark T27S R8W S34 BT. (Rec. 60 lks.)
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:
S C
T 27 S R 8 W
S 34 S 35
1961
from which new bearing trees
A Hemlock 12" dia., bears N.41°E., 6 lks. dist. mkd. T27S R8W SC BT.
A Cedar 6" dia., bears N.31½°W., 41 lks. dist. mkd. T27S R8W S34 SC BT.