

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 100304

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only; T28-1W

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5358)

-----  
Set a basalt stone 15x12x8 ins., 10" in ground for ¼ sec. cor. marked ¼ on W. face; from which  
A Fir 8" dia., bears N.70°E., 10 lks. dist. mkd. ¼ S30 BT  
A Fir 20" dia., bears West, 6 lks. dist. mkd. ¼ S25 BT.

GLO resurvey by Lincoln E. Wilkes, Cadastral Engineer; Otto L. Draper and Norman D. Price, Transitmen - Special Instructions dated Dec. 21, 1920 (Surveyed 1927-1928) - (DCSO records Vol. 24 Page(s) 10275-76)

-----  
The ¼ cor. established for secs. 25 and 30, which is a basalt stone, 12x8x5 ins., above ground, firmly set, mkd. ¼ on W. face, from which the original bearing trees

A Fir 12" dia., bears N.70°E., 10 lks. dist. mkd. ¼ S30 BT.

A Fir 24" dia., bears West 6 lks. dist. mkd. ¼ S25 BT.

I now change this corner to refer to sec. 25 only.

I destroy the markings on bearing tree in sec. 30 and take new bearing tree as follows;

A Fir 34" dia., bears N.8 3/4°W., 28 lks. dist. mkd. ¼ S25 BT.

This corner is 155 ft. above ravine.